


# THE CITY OF SANIBEL

## POST HURRICANE IAN LIFT STATION CONTROL PANEL



### PLATFORMS PROCUREMENT PHASE 1

10600 CHEVROLET WAY, SUITE 102  
ESTERO, FLORIDA 33928  
Ph: (239) 390-1467  
ENGINEERING BUSINESS NO. 2429



TETRA TECH

[www.tetratech.com](http://www.tetratech.com)



PREPARED FOR  
THE CITY OF SANIBEL

UTILITIES DEPARTMENT  
800 DUNLOP ROAD  
SANIBEL, FLORIDA 33957

MAYOR - MIKE MILLER  
VICE MAYOR - HOLLY D. SMITH  
CITY COUNCIL - RICHARD JOHNSON  
CITY COUNCIL - LAURA DeBRUCE  
CITY COUNCIL - JOHN HENSHAW

CITY MANAGER - DANA A. SOUZA  
PUBLIC WORKS DIRECTOR - ALFRED J. MITTL, PE



SHEET INDEX	
Sheet Number	Sheet Title
G-000	COVER SHEET
S-001	GENERAL NOTES
S-101	PLATFORM ON PIERS W/ LADDER
S-501	STANDARD DETAILS

PROJECT LOCATION:  
SANIBEL, FLORIDA 33957

CLIENT INFORMATION:

THE CITY OF SANIBEL  
SANIBEL, FLORIDA 33957  
Ph: (239) 472-1008 - Fax (239) 472-5531

Tt PROJECT No.:  
200-08498-24002


CLIENT PROJECT No.:

PROJECT DESCRIPTION / NOTES:  
FABRICATION OF 10 LIFT STATION PLATFORMS

ISSUED:

12/05/25 - BID SET

VICINITY MAP:



## STRUCTURAL GENERAL NOTES

- THESE GENERAL NOTES PRESENT AND/OR SUMMARIZE KEY PROJECT INFORMATION FOR THE DRAWING READER'S CONVENIENCE. SEE ALSO INDIVIDUAL DRAWING NOTES AND PROJECT SPECIFICATIONS FOR FURTHER DETAILS AND REQUIREMENTS.
- ALL REFERENCED STANDARDS HEREIN ARE TO MOST RECENT ISSUE IN EFFECT AS OF THE DATE OF THESE DOCUMENTS, UNLESS NOTED OTHERWISE IN PROJECT SPECIFICATIONS OR ON THE DRAWING.
- SUBMIT SHOP DRAWINGS, PROJECT DATA AND SAMPLES AS SPECIFIED IN PROJECT SPECIFICATIONS.
- ABBREVIATIONS

AISC	AMERICAN INSTITUTE OF STEEL CONSTRUCTION	EQ	EQUAL	O.C.	ON CENTER
APPROX.	APPROXIMATE	EW	EACH WAY	O.D.	OUTSIDE DIAMETER
B.M.	BEAM	EXIST	EXISTING	PL	PLATE
B.O.F.	BOTTOM OF FOOTING	EXP	EXPANSION	PLF	POUNDS PER LINEAR FOOT
B.O.S.	BOTTOM OF STEEL	F.V.	FIELD VERIFY	PSF	POUNDS PER SQUARE FOOT
B.S.	BOTH SIDES	FND.	FOUNDATION	PSI	POUNDS PER SQUARE INCH
BOT.	BOTTOM	FRMG	FRAMING		
BRG.	BEARING	FT	FOOT		
CCJ	CRACK CONTROL JOINT	FTG	FOOTING	QTY	QUANTITY
CJ	CONSTRUCTION JOINT	GA	GAGE, GAUGE	REF	REFERENCE
CL	CENTER LINE	GALV	GALVANIZED	REINF.	REINFORCEMENT
COL	COLUMN	GR.	GRADE	REQ/REQ	REQUIRED
CONC	CONCRETE	GRTG	GRATING	'D	
CONST	CONSTRUCTION	H.R.	HAND RAIL	REV	REVISION
CONT	CONTINUOUS	HORIZ.	HORIZONTAL	SF	SQUARE FOOT
COORD	COORDINATE	IN.	INCH	SHT.	SHEET
CTR	CENTER	INSUL	INSULATION	SIM.	SIMILAR
DIA	DIAMETER	L	ANGLE	SPEC	SPECIFICATIONS
DIM	DIMENSION	LBS	POUNDS	SQ	SQUARE
DIST	DISTANCE	LF	LINEAR FOOT (FEET)	SS	STAINLESS STEEL
DN	DOWN	MAX	MAXIMUM	STD	STANDARD
DTL.	DETAIL	MECH	MECHANICAL	STL	STEEL
DWG(S)	DRAWING(S)	MFR	MANUFACTURER	STRUCT	STRUCTURE(AL)
DWL	DOWEL	MID	MIDDLE / MIDPOINT	T/	TOP OF
E/EXIST.	EXISTING	MIN	MINIMUM, MINUTE	TEMP	TEMPORARY
EA	EACH	MISC.	MISCELLANEOUS	TYP	TYPICAL
EF	EACH FACE	MTL	METAL	UNO	UNLESS NOTED OTHERWISE
EJ	EXPANSION JOINT	N	NEW	V.I.F.	VERIFY IN FIELD
EL / ELEV.	ELEVATION	N.S.	NEAR SIDE	VERT	VERTICAL
ELEC	ELECTRIC(AL)	N.T.S.	NOT TO SCALE	W/	WITH
		NA	NOT APPLICABLE	W/O	WITHOUT
		NO	NUMBER		

## DESIGN CRITERIA

- REFERENCES:
  - ICC INTERNATIONAL BUILDING CODE, 2021 EDITION, RISK CATEGORY III IN ACCORDANCE WITH TABLE 1604.5
  - STATE BUILDING CODE: 2023 FLORIDA BUILDING CODE, BUILDING, EIGHTH EDITION
  - ASCE/SEI 7-22 - MINIMUM DESIGN LOADS FOR BUILDINGS AND OTHER STRUCTURES
- DEAD LOADS:
 

DEAD LOAD	= (SELF WEIGHT)
LOAD TO RESIST UPLIFT	= (SELF WEIGHT)
- LIVE LOADS (U.N.O.):
 

STAIRS, WALKWAYS, OR PLATFORMS	= 100 PSF
--------------------------------	-----------
- WIND LOAD:
 

BASIC DESIGN WIND SPEED, V	= 175 MPH
NOMINAL DESIGN WIND SPEED, V <sub>asd</sub>	= 136 (V <sub>ult</sub> *0.6) MPH
RISK CATEGORY	= III
WIND EXPOSURE CATEGORY	= D
DIRECTIONALITY FACTOR, K <sub>d</sub>	= 0.85
TOPOGRAPHIC FACTOR, K <sub>t</sub>	= 1.0
OPEN FRAME STRUCTURE, CF	= 1.1
DESIGN WIND FORCE, F	= 64.5 (PSF) X A <sub>f</sub>
- FLOOD LOADS: N/A FOR PLATFROM SET ABOVE DFE

## FOUNDATIONS

- NO GEOTECHNICAL/SUBSURFACE INVESTIGATION WAS PREVIOUSLY PERFORMED FOR THIS PROJECT. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO CONTRACT A GEOTECHNICAL ENGINEER TO CONFIRM ASSUMED ALLOWABLE BEARING STATED BELOW. GEOTECHNICAL ENGINEER SHALL BE RETAINED BY THE CONTRACTOR TO PROVIDE OBSERVATION AND TESTING SERVICES DURING THE GRADING AND FOUNDATION PHASE OF CONSTRUCTION. INSPECTION AND TESTING REPORTS SHALL BE SUBMITTED TO THE STRUCTURAL ENGINEER.
- ALLOWABLE BEARING PRESSURES AS FOLLOWS:
  - DEEP FOUNDATIONS: AS STABLISHED BY GEOTECHNICAL RECOMMENDATIONS. SEE PLAN FOR REQUIRED COMPRESSION, TENSION, AND LATERAL LOADS
- GEOTECHNICAL ENGINEER SHALL BE RETAINED BY THE CONTRACTOR TO PROVIDE OBSERVATION AND TESTING SERVICES DURING THE GRADING AND FOUNDATION PHASE OF CONSTRUCTION. INSPECTION AND TESTING REPORTS SHALL BE SUBMITTED TO THE STRUCTURAL ENGINEER.
- PRIOR TO PLACING ENGINEERED FILL, THE SITE SHALL BE STRIPPED AND PROOF ROLLED. ANY SOFT SPOTS ENCOUNTERED SHALL BE REMOVED AND REPLACED WITH ENGINEERED FILL. REFER TO EARTHWORK SPECIFICATION FOR ADDITIONAL INFORMATION.

## STRUCTURAL ALUMINUM

- REFERENCES:
  - AA ALUMINUM DESIGN MANUAL
  - AA ALUMINUM STANDARDS AND DATA
  - ANSI/DWS D1.2 ALUMINUM WELDING CODE
- MATERIALS:
  - PLATES AND ROLLED SHAPES: 6061-T6
  - STRUCTURAL BOLTS: 316 STAINLESS STEEL
- THE STRUCTURE IS DESIGNED TO BE SELF-SUPPORTING AND STABLE AFTER CONSTRUCTION IS FULLY COMPLETED. IT IS SOLELY THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE ERECTION PROCEDURE AND SEQUENCE AND TO ENSURE THE SAFETY OF THE BUILDING AND ITS COMPONENT PARTS DURING ERECTION. THIS INCLUDES THE ADDITION OF SHORING, SHEETING, TEMPORARY BRACING, GUYS OR TIE DOWNS WHICH MIGHT BE NECESSARY. SUCH MATERIAL SHALL REMAIN THE CONTRACTOR'S PROPERTY AFTER THE COMPLETION OF THE PROJECT.
- PROVIDE MIN. (2) 3/4" STAINLESS STEEL BOLTS (316), WASHERS, AND NUTS FOR ALL CONNECTIONS, UNLESS NOTED OTHERWISE. ALL SS BOLTS SHALL HAVE CORROSION INHIBITING GREASE AND SHALL BE SEPARATED FROM DISSIMILAR METALS TO PREVENT CORROSION.
- ALL WELDING SHALL CONFORM TO AWS D1.2. SHOP DRAWINGS SHALL SHOW ALL SHOP AND ERECTION DETAILS INCLUDING CUTS, COPE CONNECTIONS, HOLES, THREADED FASTENERS, RIVETS, AND WELDS. GRIND ALL WELDS FOR SMOOTH TRANSITIONS.
- THE APPROVAL OF THE SHOP DRAWINGS WILL BE FOR SIZE AND ARRANGEMENT OF PRINCIPAL AND AUXILIARY MEMBERS AND STRENGTH OF CONNECTIONS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DIMENSIONS SHOWN ON THE SHOP DRAWINGS.
- LAYOUT AND DESIGN FOR GUARDRAIL, HANDRAIL AND THEIR COMPONENTS SHALL ADHERE TO THE APPLICABLE BUILDING CODES.
- BURNING OF HOLES IN ALUMINUM IS NOT PERMITTED WITHOUT PRIOR APPROVAL OF THE ENGINEER.
- ALL ALUMINUM IN CONTACT WITH CONCRETE SHALL BE COATED WITH BITUMINOUS PAINT.

## DEFERRED SUBMITTALS

- IN ACCORDANCE WITH THE SPECIFICATIONS DESIGNS FOR THE ITEMS LISTED BELOW ARE NOT INCLUDED IN THE CONTRACT DOCUMENTS. DESIGN OF THESE ELEMENTS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR, AND SHALL BE DESIGNED AND SEALED BY A REGISTERED PROFESSIONAL ENGINEER LICENSED IN THE STATE OF FLORIDA:
  - ALUM. GUARDRAIL AND HANDRAIL SYSTEMS AND THEIR CONNECTIONS
  - ALUM. LADDERS AND PLATFORM DETAILS AND ATTACHMENTS
  - ALUM. GRATING AND CHECKER PLATE SURFACES (DESIGN FOR MINIMUM SIZES PROVIDED)
  - FOUNDATION SYSTEM (DEEP OR SHALLOW) IN ACCORDANCE WITH GEOTECHNICAL INVESTIGATION
- DESIGN OF THE ITEMS LISTED ABOVE SHALL BE IN ACCORDANCE WITH THE ICC INTERNATIONAL BUILDING CODE, 2021 EDITION, FLORIDA BUILDING CODE, 2023 EDITION, OSHA AND SHALL INCLUDE ALL ATTACHMENTS TO THE STRUCTURE

**TETRA TECH**  
ENGINEERING BUSINESS NO. 2429  
10600 CHEVROLET WAY, SUITE 102  
TEL: (239) 390-1487 FAX: (239) 390-1799

**TETRA TECH**  
www.tetratech.com  
10600 CHEVROLET WAY, SUITE 102  
TEL: (239) 390-1487 FAX: (239) 390-1799

BID SET

TTUS. J. MADDELA, P.E.  
LICENSE #22624  
4910 Brownboro Rd, Ste 245  
Engineering Business No. 2429  
DATE: 12/05/2025

BY



