

# CITY OF SANIBEL

## CITY HALL HVAC REPLACEMENT

800 DUNLOP RD, SANIBEL, FL 33957



Weston & Sampson<sup>SM</sup>

Weston & Sampson Engineers, Inc.  
4210 Metro Parkway, Suite 230  
Fort Myers, FL 33916  
978.532.1900 800.SAMPSON

[www.westonandsampson.com](http://www.westonandsampson.com)

SHEET INDEX	
SHEET NO.	SHEET DESCRIPTION
M001	MECHANICAL NOTES & SCHEDULE
M101	MECHANICAL PLAN
E001	ELECTRICAL NOTES & SYMBOLS
E101	POWER & SYSTEMS PLANS
E201	PANEL SCHEDULES, CALCULATION...



Location Map

Issue Date: 8/8/2025

Issued For: BIDS



## HVAC SYMBOLS

## ABBREVIATIONS

## GENERAL NOTES AND SPECIFICATIONS

	DIFFUSER TAG: <u>DIFFUSER TYPE</u> CFM		THERMOSTAT		EXHAUST FAN		CEILING DIFFUSER (SUPPLY)		CEILING DIFFUSER (RETURN)		WALL MOUNTED DIFFUSER, GRILLE, OR LOUVER (SUPPLY)		WALL MOUNTED DIFFUSER, GRILLE, OR LOUVER (RETURN)		SPIN-IN, SADDLE TAP FITTING WITH DAMPER		SPIN-IN, SADDLE TAP FITTING WITHOUT DAMPER		REVISION SYMBOL		KEY NOTE (SEE KEY NOTES ON PLANS SHEETS)		REFR	REFRIGERANT LINE																																																																																				
	<u>SINGLE LINE DUCTWORK</u>		HORIZONTAL DUCT		<u>DOUBLE LINE DUCTWORK</u>		SUPPLY DUCT, TURNING UP		RETURN DUCT, TURNING UP		CONCENTRIC DUCT TRANSITION		ECCENTRIC DUCT TRANSITION		RECTANGULAR DUCT ELBOW WITH TURNING VANES		RECTANGULAR DUCT TEE WITH TURNING VANES		DUCT SMOKE DETECTOR		VOLUME DAMPER		MOTORIZED VOLUME DAMPER		FLEXIBLE DUCT																																																																																			
	Ø DIAMETER		A/C AIR CONDITIONING		MFR	MANUFACTURER		THE ME THE STA		MAX	MAXIMUM		MBH	BTU X 1,000		MECHANICAL		AIR HANDLING UNIT		MECH	MECHANICAL		AUTHORITY HAVING JURISDICTION		MIN	MINIMUM		AMERICAN SOCIETY OF HEATING, REFRIGERATION, AND AIR CONDITIONING ENGINEERS		LV	LOW VOLTAGE		BTUH BRITISH THERMAL UNIT PER HOUR		MS	MOTION SWITCH		CD CONDENSATE DRAIN		OA	OUTSIDE AIR		CFM CUBIC FEET PER MINUTE		O/H	OVER HEAD		CLG CEILING		REQ'D	REQUIRED		Cu COPPER		RTU	ROOF TOP UNIT		CU CONDENSER UNIT		SBCCI	SOUTHERN BUILDING CODE CONGRESS INTERNATIONAL		DWG DRAWING		SMACNA	SHET METAL AND AIR CONDITIONING CONTRACTOR'S NATIONAL ASSOCIATION		EF EXHAUST FAN		SS	STAINLESS STEEL		ESP EXTERNAL STATIC PRESSURE		TC	TIME CLOCK		EXH EXHAUST		TSTAT	THERMOSTAT		FC FAN COIL		UNO	UNLESS NOTED OTHERWISE		HGT HEIGHT		UL	UNDERWRITERS LABORATORIES		HTR HEATER		VAV	VARIABLE AIR VOLUME		HP HORSE POWER		W/	WITH		HVAC HEATING, VENTILATING, AND AIR CONDITIONING		W/O	WITH OUT		KW KILOWATT
<b>FLEX DUCT RUNOUT NOTES</b>																																																																																																												
<ol style="list-style-type: none"> <li>1. TYPICAL FOR ALL RUN OUTS FROM MAIN SUPPLY (OR RETURN) DUCT TO DIFFUSER. PROVIDE WITH ROUND SPIN-IN WITH DAMPER AT DUCT CONNECTION. RUN DUCT IN EXTERNALLY INSULATED GALVANIZED SHEET METAL SNAP-LOK UP TO WITHIN 5' OF DIFFUSER. MAKE FINAL CONNECTION TO DIFFUSER WITH INSULATED FLEX DUCT. NO MORE THAN 5' OF FLEX DUCT MAY BE USED. ROUND DUCT AND FLEXIBLE DUCT SHALL MATCH DIFFUSER NECK SIZE (WHERE ROUND). FOR ALL OTHER GRILLES WITHOUT ROUND NECK, SIZE SHALL BE PER FOLLOWING RUN OUT SCHEDULE:           <table style="margin-left: 20px;"> <tr><td>4"</td><td>- 0 TO 50 CFM</td></tr> <tr><td>6"</td><td>- 51 TO 125 CFM</td></tr> <tr><td>8"</td><td>- 126 TO 225 CFM</td></tr> <tr><td>10"</td><td>- 226 TO 350 CFM</td></tr> <tr><td>12"</td><td>- 351 TO 600 CFM</td></tr> </table> </li> <li>2. ALL DIFFUSER CONNECTIONS LARGER THAN 600 CFM SHALL BE MADE FULL DUCT SIZE AS INDICATED ON PLANS TO DIFFUSER.</li> </ol>															4"	- 0 TO 50 CFM	6"	- 51 TO 125 CFM	8"	- 126 TO 225 CFM	10"	- 226 TO 350 CFM	12"	- 351 TO 600 CFM																																																																																				
4"	- 0 TO 50 CFM																																																																																																											
6"	- 51 TO 125 CFM																																																																																																											
8"	- 126 TO 225 CFM																																																																																																											
10"	- 226 TO 350 CFM																																																																																																											
12"	- 351 TO 600 CFM																																																																																																											

## EX DUCT RUNOUT NOTES

1. TYPICAL FOR ALL RUN OUTS FROM MAIN SUPPLY (OR RETURN) DUCT TO DIFFUSER. PROVIDE WITH ROUND SPIN-IN WITH DAMPER AT DUCT CONNECTION. RUN DUCT IN EXTERNALLY INSULATED GALVANIZED SHEET METAL SNAP-LOK UP TO WITHIN 5' OF DIFFUSER. MAKE FINAL CONNECTION TO DIFFUSER WITH INSULATED FLEX DUCT. NO MORE THAN 5' OF FLEX DUCT MAY BE USED. ROUND DUCT AND FLEXIBLE DUCT SHALL MATCH DIFFUSER NECK SIZE (WHERE ROUND). FOR ALL OTHER GRILLES WITHOUT ROUND NECK, SIZE SHALL BE PER FOLLOWING RUN OUT SCHEDULE:
  - 4" - 0 TO 50 CFM
  - 6" - 51 TO 125 CFM
  - 8" - 126 TO 225 CFM
  - 10" - 226 TO 350 CFM
  - 12" - 351 TO 600 CFM
2. ALL DIFFUSER CONNECTIONS LARGER THAN 600 CFM SHALL BE MADE FULL DUCT SIZE AS INDICATED ON PLANS TO DIFFUSER.
11. ALL EQUIPMENT INDICATED SHALL BE BALANCED AND OF SIMILAR EQUIPMENT. OCCUPANCY AND MANUFACTURER THE SAME. ALL BEING THE SAME. ALL CONDITIONS MANUFACTURED THE SAME.

CHANICAL CONTRACTOR SHALL COMPLY WITH THE 2023 FLORIDA BUILDING CODE (8TH EDITION), STATE OF FLORIDA ENERGY CODE, AND ALL LOCAL CODES AS MAY BE APPLICABLE.

ICAL PLANS ARE DIAGRAMMATIC ONLY. THEY ARE INTENDED TO INDICATE CAPACITY, SIZE, IN, DIRECTION, AND GENERAL ARRANGEMENT, BUT NOT EXACT DETAILS OF CONSTRUCTION. THE THAT ONLY CERTAIN FEATURES OF THE INSTALLATION ARE INDICATED MUST NOT BE TAKEN TO THAT OTHER SIMILAR OR DIFFERENT FEATURES WILL NOT BE REQUIRED. ALL RISES AND DROPS NG AND DUCTWORK NOT NECESSARILY SHOWN.

SHALL INCLUDE ALL LABOR, MATERIALS, PERMITS AND OTHER COSTS AS ARE NECESSARY FOR STALLATION OF A COMPLETE AND SATISFACTORY OPERATIONAL AIR CONDITIONING SYSTEM.

DRAWINGS SHALL BE PROVIDED FOR ALL MECHANICAL EQUIPMENT THAT IS TO BE USED ON THIS T WHETHER OR NOT THE EQUIPMENT IS SPECIFICALLY SPECIFIED IN THESE DOCUMENTS. THIS ES (BUT IS NOT LIMITED TO) HVAC EQUIPMENT & SUPPORTS, DIFFUSERS/GRILLES/LOUVERS, WORK & SUPPORTS, REFRIGERANT LINES, INSULATION, HVAC SPECIALTIES (COLLARS, FIRE S, BALANCING DAMPERS ETC.) CONTROLS & CABLING, ETC.. SHOP DRAWINGS SHALL BE ED PRIOR TO ORDERING OR ANY INSTALLATION OF EQUIPMENT. ANY EQUIPMENT NOT INCLUDED SHOP DRAWING SUBMITTALS, SHALL BE PROVIDED PER THE PLANS AND SPECIFICATIONS.

TALS ARE TO BE TOTAL & COMPLETE. INCOMPLETE OR PIECemeAL SHOP DRAWINGS WILL NOT Eviewed UNTIL ALL SUBMITTALS ARE PROVIDED. ALL EQUIPMENT (INCLUDING ANY/ALL OPTIONS) BE CLEARLY SELECTED/INDICATED ON THE CUTSHEETS INCLUDED IN THE SUBMITTAL.

TALS SHAL BE PROVIDED IN PDF FORMAT.

DRAWINGS SUBMITTED BY WAY OF AN ELECTRONIC PROJECT MANAGEMENT SYSTEM ARE NOT ABLE.

ONTRACTOR SHALL COORDINATE WITH THE OTHER CONTRACTORS TO INSURE THAT EACH TRADE HAVE SUFFICIENT SPACE TO INSTALL THEIR EQUIPMENT (DUCTWORK, PIPING, ELECTRICAL, ETC.).

ALL DIMENSIONS FROM ARCHITECTURAL PLANS OR FIELD DIMENSIONS.

NOTED, ALL MATERIALS SHALL BE NEW, COMPLETE, INCLUDE MANUFACTURER'S WARRANTY, AND APPROVED IF APPLICABLE. ALL WORK SHALL PRESENT A NEAT MECHANICAL APPEARANCE WHEN TED.

CTOR SHALL FURNISH AND INSTALL CURBS AND BASES FOR ALL EQUIPMENT AS SHOWN ON THIS CONTRACTOR SHALL CONFIRM ALL CURB REQUIREMENTS AND THEIR SIZES.

E INSULATION FOR REFRIGERANT LINES SIMILAR TO ARMAFLEX. WEATHER-EXPOSED INSULATION PROVIDED WITH WEATHER PROOF COATING AS RECOMMENDED BY MANUFACTURER. EXPOSED ISATE LINES THOSE CONCEALED IN WALLS AND CEILINGS TO BE PROVIDED WITH SAME TYPE OF ION.

ENT AS PER SCHEDULED LIST OF ACCEPTABLE MANUFACTURERS:

UPMENT: TRANE, DAIKIN

IRLLES: CLEAN AND REUSE EXISTING

CLEAN AND REUSE EXISTING

S: CLEAN AND REUSE EXISTING

UPMENT SHALL BE STARTED, TESTED, ADJUSTED AND BALANCED FOR AIR DELIVERY AS ED ON THE PLANS, AND PLACED IN SATISFACTORY OPERATIONAL CONDITION BY A TEST AND E COMPANY WHOSE SOLE BUSINESS IS THE TESTING, ADJUSTING AND BALANCING OF SYSTEMS LAR SIZE AND TYPE. THIS CONTRACTOR SHALL GUARANTEE ALL WORKMANSHIP, MATERIALS AND ENT TO BE FREE OF DEFECTS FOR A PERIOD OF ONE YEAR FROM DATE OF CERTIFICATE OF NCY. THIS IS IN ADDITION TO ANY WARRANTY OR GUARANTEE FROM THE EQUIPMENT CTRACTURER. FURNISH THE OWNER WITH THE MANUFACTURER'S WRITTEN WARRANTY CERTIFICATES. MECHANICAL CONTRACTOR IS RESPONSIBLE FOR PROVIDING ONE BELT AND SHEAVE CHANGE ON LT DRIVEN EQUIPMENT FOR BALANCING PURPOSES.

CONTROLS ARE TO BE TESTED AND CALIBRATED SO AS TO BE OPERATING WITH THE CTRACTURER'S SPECIFICATIONS. ANY DEFECTIVE UNITS ARE TO BE REPLACED.

2. ALL EQUIPMENT SHALL BE PROPERLY SUPPORTED AND ISOLATED TO PREVENT NOISE AND VIBRATION TRANSMISSION. ALL AIR HANDLING EQUIPMENT SHALL BE SUPPORTED WITH SPRING ISOLATORS. ALL CONNECTIONS BETWEEN AIR HANDLING EQUIPMENT AND DUCTWORK SHALL BE CANVAS FLEXIBLE CONNECTORS FOR ALL SYSTEMS ABOVE 5 NOMINAL TONS IN SIZE.
3. PROVIDE SPRING ISOLATORS FOR ALL TRUSS MOUNTED EXHAUST FANS.
4. ALL EQUIPMENT SHALL BE LOCATED WITHIN THE MECHANICAL ROOM AND CEILING SPACES WITH ADEQUATE CLEARANCES FOR REPAIR AND MAINTENANCE. ALL PIPING AND DUCTWORK SHALL BE INSTALLED TO PROVIDE ADEQUATE CLEARANCE FOR ACCESS TO ALL EQUIPMENT. CONTRACTOR SHALL ENSURE THAT NO TRANSGRESSION OF THIS SPACE IS MADE BY OTHER CONTRACTORS.
5. ALL CONTROL WIRING SHALL BE IN CONDUIT. WHERE CONTROL WIRING IS CONCEALED BY CEILING STRUCTURE, WIRING MAY BE PLENUM RATED CABLE. ALL CONTROL WIRING SHALL BE SECURELY ATTACHED TO THE STRUCTURE AT A MAXIMUM SPACING OF EVERY FOUR FEET.
6. DUCT DIMENSIONS SHOWN ON DRAWINGS ARE CLEAR INSIDE DIMENSIONS. IN GENERAL, ALL PIPING AND DUCTWORK SHALL BE RUN CONCEALED IN CEILING SPACES PROVIDED UNLESS NOTED OR INDICATED OTHERWISE. ROUTING SHALL BE COORDINATED WITH OTHER TRADES. DO NOT INSTALL ANY DUCTWORK OR PIPING OF ANY KIND ABOVE ELECTRICAL PANEL.
7. ALL DUCTWORK, INSTALLATION AND EQUIPMENT SHALL MEET THE LATEST ADOPTED EDITION OF THE STATE OF FLORIDA ENERGY CODE.
8. METAL DUCTWORK SHALL BE FABRICATED, SUPPORTED AND INSTALLED IN STRICT ACCORDANCE WITH THE LATEST EDITION OF SMACNA'S "HVAC DUCT CONSTRUCTION STANDARDS – METAL AND FLEXIBLE" TO A MINIMUM OF 2" PRESSURE CLASSIFICATION AND CLASS B SEAL. SQUARE DUCTWORK WITHIN 5' OF DISCHARGE AND THE ENTIRE RETURN DUCTWORK SHALL BE INTERNALLY INSULATED WITH 1 1/2" FIBERGLASS INSULATION EQUAL TO JOHNS MANVILLE "PERMACOUSTIC". THE REST OF THE DUCTWORK SHALL BE EXTERNALLY INSULATED WITH 2" THICK DUCTWRAP WITH FOIL FACING. .
9. RIGID FIBERGLASS DUCTBOARD WITH ANTIMICROBIAL COATING AND 1-1/2" R-6 INSULATION IN ACCORDANCE WITH SMACNA "FIBROUS GLASS DUCT CONSTRUCTION STANDARDS".
10. HVAC SUPPLY DIFFUSERS AND RETURN GRILLES SHALL BE TITUS WITH WHITE FINISH, ALUMINUM CONSTRUCTION. SEE PLANS FOR THROAT CONNECTION SIZES.
11. CONTRACTOR TO PROVIDE ENERGY MANAGEMENT SYSTEM FOR MONITORING OF ALL HVAC EQUIPMENT. SEE SEQUENCE OF CONTROLS NOTES FOR MORE DETAILS OF SYSTEM.
12. THESE CONTRACT DOCUMENTS REPRESENT A PORTION OF A COMPLETE DESIGN WHICH, TO THE BEST OF OUR KNOWLEDGE HAVE BEEN PREPARED IN COMPLIANCE WITH APPLICABLE BUILDING CODE REQUIREMENTS. THE USE OF THESE PLANS WITHOUT THE CONSENT OF THE ENGINEER OF RECORD IS PROHIBITED. ALTERATIONS TO THE DESIGN AS SHOWN ON THESE PLANS ARE ONLY ALLOWED BY WRITTEN AUTHORIZATION OF THE ENGINEER OF RECORD.
13. H.V.A.C. CONTRACTOR SHALL PROVIDE ONE SET OF CUTSHEETS OF ALL SELECTED EQUIPMENT TO ELECTRICAL CONTRACTOR TO ADJUST CIRCUIT REQUIREMENTS (IF REQUIRED) BASED ON ACTUAL SELECTED MANUFACTURER'S DATA.
14. CONTRACTOR SHALL COORDINATE WORK WITH OTHER TRADES. REFERENCE ENTIRE SET OF CONSTRUCTION DOCUMENTS IN INSTALLATION OF MECHANICAL SYSTEMS INCLUDING ARCHITECTURAL, STRUCTURAL, ELECTRICAL, PLUMBING AND FIRE SPRINKLERS.
15. CONTRACTOR SHALL INSTALL DUCT SMOKE DETECTOR IN SUPPLY WHERE INDICATED ON PLANS OR AS REQUIRED BY CODE AND AUTHORITY HAVING JURISDICTION. DUCT SMOKE DETECTOR SHALL BE COMPATIBLE WITH FIRE ALARM MONITORING SYSTEM.
16. THESE PLANS MAKE REFERENCE TO EXISTING CONDITIONS. CONTRACTOR SHALL VISIT SITE WITH RESPECT TO PROPOSED CONSTRUCTION PRIOR TO BID. NOTIFY ENGINEER OF ANY DISCREPANCIES.
17. CONTRACTOR MAY USE SALVAGEABLE PORTIONS OF EXISTING RIGID DUCTWORK.
18. PROVIDE 1 HOUR FIRE DAMPER AT ALL PENETRATIONS THROUGH RATED WALL ASSEMBLIES.

## **TEMPORARY COOLING REQUIREMENTS**

1. THE MECHANICAL CONTRACTOR SHALL WORK ON ONE OF THE MAIN HVAC SYSTEMS WITHIN THE IT ROOM AND FINANCE DEPARTMENT SPACE AT A TIME. THE OTHER SYSTEMS SHALL REMAIN IN OPERATION AT ALL TIMES TO PROVIDE COOLING TO THE SPACES.
2. CONTRACTOR SHALL PLAN AND SCHEDULE WORK FOR WEEKEND CHANGEOVER OF AHU-1/2, SUCH THAT AT LEAST ONE OF THE UNITS IS OPERATIONAL FOR NORMAL BUSINESS HOURS. UNITS SHALL OPERATE ON UNIT CONTROLS UNTIL ENERGY MANAGEMENT SYSTEM CAN BE INSTALLED TO TAKE OVER CONTROL OF UNITS.
3. CONTRACTOR SHALL PLAN AND SCHEDULE WORK FOR IT ROOM AIR CONDITIONER REPLACEMENT, SUCH THAT THE EXISTING OPERATIONAL A/C SYSTEM IN THE SPACE CONTINUES IN OPERATION WHILE 1 OF THE NEW UNITS IS INSTALLED. AFTER THE NEW UNIT IS UP AND OPERATIONAL, THE SECOND REDUNDANT SYSTEM, CONTROLS AND ENERGY MANAGEMENT SYSTEM SHALL BE INSTALLED.
4. CONTRACTOR SHALL PROVIDE A MINIMUM OF (6) TEMPORARY ROOM/SPACE AIR CONDITIONING UNITS IN THE WORKING AREAS DURING DEMOLITION AND CONSTRUCTION. TEMPORARY UNITS MAY BE A COMBINATION OF WINDOW UNITS FOR INDIVIDUAL OFFICES WITH EXTERIOR WINDOWS AND FREE STANDING PORTABLE UNITS. TEMPORARY UNITS' TONNAGE SHALL MATCH OR EXCEED THAT OF REMOVED UNITS BEING REPLACED. CONDENSATE REMOVAL, HOSES, AND FLEXIBLE EXHAUST DUCT SHALL BE PROVIDED TO AN EXTERIOR OPENING.
5. COORDINATE CIRCUITS USED WITH AREA SO AS NOT TO SHUT SYSTEMS OFF WITH CITY OF SANIBEL PROJECT MANAGER.
6. ADEQUATE TEMPORARY COOLING SHALL ALSO BE PROVIDED FOR ALL OTHER AREAS DURING HVAC SYSTEM REPLACEMENT.
7. CONTRACTOR WILL BE REQUIRED TO SUBMIT A PHASED WORK PLAN, INCLUDING PROVISIONS FOR TEMPORARY AIR CONDITIONING UNITS (INCLUDING PROPOSED TYPE OF TEMPORARY UNITS) FOR ENGINEER AND OWNER APPROVAL PRIOR TO COMMENCEMENT OF WORK.

## FAN SCHEDULE F

1. PROVIDE WITH BACKDRAFT DAMPER
2. ELECTRONIC SPEED CONTROL MOUNTED IN CABINET
3. ACTIVATE VIA MOTION SENSOR

#### SPI IT SYSTEM HEAT PUMP SCHEDULE

SPLIT SYSTEM HEAT PUMP SCHEDULE																									
GENERAL			AIR HANDLER									CONDENSING UNIT						SYSTEM DATA							
NO.	LOCATION SERVED	MFG	MARK	MODEL	CFM		FAN		HEATER		ELECTRICAL			MARK	MODEL	ELECTRICAL			COMPRESSOR		COOL CAPACITY		HSPF	SEER	REMARKS
					TOTAL	OA	ESP	FLA	MODEL	MBTUH	VOLTS	MCA	MOP			VOLTS	MCA	MOP	NO	TONS	TMBH	SMBH			
1	LOUNGE 021	DAIKIN	AHU-3	FTXM24WVJU9	475	-	-	-	HEATPUMP	-	230/1	-	-	CU-3	RXM24WVJU9	230/1	22.0	30	1	2.0	21.6	-	10.0	22.0	1 - 4
2	IT RM	DAIKIN	AHU-4/5	FTXM24WVJU9	475	-	-	-	HEATPUMP	-	230/1	-	-	CU-4/5	RXM24WVJU9	230/1	22.0	30	1	2.0	21.6	-	10.0	22.0	1 - 4


REMARKS

1. DUCTLESS SPLIT SYSTEM HEAT PUMP POWERED FROM THE CONDENSING UNIT VIA THE INDOOR CEILING MOUNTED AIR HANDLER.
2. THE UNIT IS EQUIPPED TO OPERATE AT LOW AMBIENT COOLING DOWN TO 0 TO 115 DEGREE (F) AND LOW AMBIENT HEATING DOWN TO -13 TO 75 DEGREE (F).
3. PROVIDE UNIT WITH BACNET COMMUNICATION CARD FOR INTERCONNECTION CAPABILITY TO ENERGY MANAGEMENT SYSTEM AND TEMPERATURE CONTROLLER ON WALL IN SPACE.
4. PROVIDE CONDENSER FIN COATING 7500 HOUR SALT SPRAY COATING BY PLYCOLD OR EQUAL PRIOR TO INSTALLATION.

SPIDER SYSTEM SCHFDUI F

SPLIT SYSTEM SCHEDULE																								
GENERAL			AIR HANDLER									CONDENSING UNIT						SYSTEM DATA						
NO.	LOCATION SERVED	MFG	MARK	MODEL	CFM		FAN		HEATER		ELECTRICAL			MARK	MODEL	ELECTRICAL			COMPRESSOR		CAPACITY		SER	REMARKS
					TOTAL	OA	ESP	FLA	MODEL	KW	VOLTS	MCA	MOP			VOLTS	MCA	MOP	NO	TONS	TREH	SMRH		
1	OFFICES	TRANE	AHU-1/2	TWE072K3BAA	2,200	250	1	6.8	BAYHTRR315	11.24	208/3	48.00	50	CU-1/2	TTA072K3DAA	208/3	33.0	45	2	6.0	74.0	55.0	1.5	1,2
REMARKS																								

1. HORIZONTAL DISCHARGE AIR HANDLER. PROVIDE WITH TX VALVE. FACTORY MOUNTED ELECTRIC HEATER WITH SINGLE POINT POWER CONNECTION. PROVIDE TIME DELAY RELAY, SUMP HEATER AND START ASSIST CAPACITOR FOR CONDENSING UNITS. REFRIGERANT LINE SIZES PER MANUFACTURER'S RECOMMENDATIONS BASED ON ACTUAL RUN LENGTH. PROVIDE WITH 2" FLAT FILTER INSTALLED IN UNIT. PROVIDE AND INSTALL AIR PLUS CLEANER MODEL FM-6000, INSTALLATION PER MANUFACTURER'S INSTRUCTION.
2. CONDENSING UNITS TO BE PROVIDED WITH 7500 HOUR SALT SPRAY BY BLYGOLD OR EQUAL. AIR HANDLER TO BE PROVIDED WITH STAND-ALONE DDC CONTROLS WITH BACNET COMMUNICATION FOR COMMUNICATION WITH ENERGY MANAGEMENT SYSTEM. PROVIDE WITH SINGLE ZONE VAV CONTROLLER, WALL SENSORS AND REMOTE SENSOR FOR AVERAGING.



AS BEEN DIGITALLY SIGNED AND  
MARK A. BRANT, PE, ON 8/5/2025.  
  
PIES OF THIS DOCUMENT ARE  
ERRED SIGNED AND SEALED AND  
URE MUST BE VERIFIED ON ANY

PIES OF THIS DOCUMENT ARE  
ERED SIGNED AND SEALED AND  
URE MUST BE VERIFIED ON ANY

# MECHANICAL NOTES & SCHEDULES

---

© 2010 Nunhems

# M001





Weston &amp; Sampson


Weston & Sampson Engineers, Inc.  
4210 Metro Parkway, Suite 230  
Fort Myers, FL 33919  
239.437.4601 800.SAMPSON  
www.westonandsampson.com

Consultants:

**BURGESS BRANT**  
CONSULTING ENGINEERS  
12935 S. CLEVELAND AVENUE SUITE 229  
FORT MYERS, FL 33912  
(239) 274-0020 (239) 274-0021 (FAX)  
EMAIL: BBCE@BURGESSBRANT.COM  
CERTIFICATE OF AUTHORIZATION #6032  
JOSEPH W BROUGHTON, PE #63949  
MARK A BRANT, PE #54692



DDC CONTROLS		MECHANICAL KEYNOTES	
<b>FRONT END CONTROLLER</b>	<b>AHU-1 &amp; AHU-2</b>		
1. PROVIDE NEW HARDWARE AND SOFTWARE CONSISTING OF MAIN ENERGY MANAGEMENT CONTROL PANEL AND SPLIT SYSTEM CONTROLLERS. MAIN ENERGY MANAGEMENT FRONT END PANEL FOR BUILDING AUTOMATION SYSTEM TO MONITOR ALL OTHER SYSTEMS AND BE EXPANDABLE TO INCLUDE ALL EXISTING A/C SYSTEMS IN THE FUTURE. FIELD VERIFY ALL EXISTING LOCATIONS OF AIR CONDITIONING SYSTEMS. AT THIS TIME, ONLY THE NEW IT ROOM AND NEW SPLIT SYSTEMS TO BE MONITORED BY ENERGY MANAGEMENT SYSTEM.	PROVIDE INTERCONNECTION WITH UNIT SUPPLIED BACNET COMPATIBLE CONTROLLERS. PROVIDE THE FOLLOWING POINTS AND ADDITIONAL POINTS OF MONITORING WHERE UNIT CONTROLLER DOES NOT PROVIDE CONTROL POINT INDICATED BELOW.	1. EXISTING AIR DEVICES AND EXISTING DUCTWORK TO REMAIN AND BE REUSED, EXCEPT AS NOTED. REBALANCE AIR FLOW TO CFM INDICATED. PROVIDE A COMFORT BALANCE AFTER NEW EQUIPMENT TO BALANCE TO +/- 2°F BETWEEN SPACES.	
2. PROVIDE NEW DEDICATED COMPUTER FOR THE BUILDING WITH GRAPHIC USER INTERFACE THAT INCLUDES ZONING FOR ALL SPACES FOR THE ENTIRE BUILDING, SUCH THAT ENERGY MANAGEMENT SYSTEM MAY BE MONITORED REMOTELY FROM ANY REMOTE INTERNET CONNECTED COMPUTER.	1. SPACE TEMPERATURE 2. SPACE TEMPERATURE SETPOINT 3. COOLING STAGE 1 ON/OFF 4. COOLING STAGE 2 ON/OFF 5. HEATING STAGE 1 ON/OFF 6. FAN SPEED (SINGLE ZONE CONTROL) 7. FAN STATUS (ON/OFF) 8. EVAPORATOR FAN POWER VERIFIED (CT SWITCH) 9. CONDENSER POWER ON/OFF (CT SWITCH) 10. LEAVING AIR TEMPERATURE 11. REMOTE SPACE AVERAGING/MONITORING SENSOR 12. SCHEDULING (OCCUPIED/UNOCCUPIED)	2. EXISTING SUPPLY, RETURN AND OUTSIDE AIR DUCTS SHALL BE RECONNECTED TO NEW AIR HANDLERS AND BALANCED TO CFM AS NOTED.	
3. SELECTED CONTROLS SYSTEM MUST HAVE OFFICE FOR REPAIR, MAINTENANCE AND INSTALLATION WITHIN 100 MILES OF THE SITE.		3. EXISTING DIFFUSER TO REMAIN AND BE CLOSED OFF TO 0 CFM. AT TIME OF TEMPERATURE BALANCING, DIFFUSER MAY BE OPENED UP TO SUPPLEMENT ROOM AIR CONDITIONING.	
4. PROVIDE SOFTWARE USING GRAPHIC USER INTERFACE AND COLOR SCHEMATIC. THE SOFTWARE SHALL AT A MINIMUM HAVE BUILDING FLOOR PLAN, ZONES, AIR HANDLING UNITS AND CONDENSING UNITS. COLOR CODED ZONES SHALL SHOW WHERE SPACE TEMPERATURES ARE OUTSIDE OF SPACE TEMPERATURE SETPOINTS AND OCCUPIED/UNOCCUPIED SCHEDULE. COORDINATE WITH OWNER FOR HOURS OF OPERATION FOR SCHEDULE AND SPACE TEMPERATURE SETPOINT.		4. EXISTING AIR HANDLING, CONDENSING UNITS, AND REFRIGERATION LINES SHALL BE DISCONNECTED, REMOVED AND REPLACED WITH ALL NEW HVAC SYSTEMS. NEW REFRIGERATION LINES SHALL USE THE SAME ROUTE AS REMOVED LINES, COORDINATE IN THE FIELD.	
5. PROVIDE OWNER WITH MINIMUM OF 8 HOURS OF TRAINING ON CONTROL SYSTEM.		5. PROVIDE AND INSTALL MINISPLIT WITH CONDENSING UNIT, NEW REFRIGERATION LINE, THERMOSTAT, CONDENSATE DRAIN LINE INTO EXISTING DRAIN. VERIFY ROUTING AND LOCATION IN THE FIELD.	
6. ALL CONTROL WIRING USED FOR CONTROL SYSTEM MUST BE WITH PLENUM RATED CABLE WHERE INSTALLED ABOVE ACCESSIBLE CEILINGS AND CONDUIT IN IN ACCESSIBLE CEILING.		6. AHU-1/2 SHOWN IN LOCATION FOR CLARITY PURPOSES.	
7. MAIN FRONT END CONTROL SYSTEM AS PER SCHEDULED LIST OF ACCEPTABLE PROVIDERS: TRIDUM, ALERTON, AUTOMATED LOGIC, DISTECH.		7. ACTUAL LOCATION OF AHU-1/2 STACKED OVER EACH OTHER.	
ALTERNATE CONTROL SYSTEMS WILL BE CONSIDERED. IF AN ALTERNATE CONTROL MANUFACTURE IS PROPOSED, CONTROLS CONTRACTOR SHALL SCHEDULE TIME TO MEET WITH CITY OF SANIBEL TO SHOW CAPABILITIES OF THE SYSTEM FOR THE CITY OF SANIBEL'S APPROVAL.		8. EXISTING BATHROOM FANS AND DUCTWORK SHALL BE REMOVED. INSTALL NEW EXHAUST FANS AND DUCTWORK, CONNECT TO EXISTING DUCT THAT EXITS THE BLDG. VERIFY AND COORDINATE ROUTING IN THE FIELD.	
8. AHU-3		9. EXISTING TEMPERATURE CONTROL SHALL BE REPLACED WITH NEW DIGITAL TEMPERATURE CONTROLLER WITH 7 DAY PROGRAMMABLE FUNCTION. TEMPERATURE ADJUSTMENT AND SINGLE ZONE VAV CONTROL. PROVIDE REMOTE SENSORS AT LOCATION INDICATED FOR AVERAGING. PROVIDE BACNET CONTROLS AND INTERCONNECTED WITH NEW FRONT END ENERGY MANAGEMENT SYSTEM PER SEQUENCE OF CONTROLS DRAWINGS.	
PROVIDE INTERCONNECTION WITH UNIT BACNET CARD AND PULL AND PROVIDE THE FOLLOWING POINTS OF CONTROL AND MONITORING.	1. SPACE TEMPERATURE 2. SPACE TEMPERATURE SETPOINT 3. COOLING AHU-4 (ON/OFF) 4. COOLING AHU-5 (ON/OFF) 5. CONDENSING UNIT POWER ON/OFF MONITORED (CT SWITCH) (CU-4) 6. CONDENSING UNIT POWER ON/OFF MONITORED (CT SWITCH) (CU-5) 7. SCHEDULING (OCCUPIED/UNOCCUPIED) 8. LEAD/LAG SYSTEM WHEREBY THE LEAD AND LAG SYSTEM ALTERNATE EVERY WEEK OR UPON FAILURE OF LEAD SYSTEM. 9. EVAPORATOR LEAVING AIR TEMPERATURE (AHU-4) 10. EVAPORATOR LEAVING AIR TEMPERATURE (AHU-5) 11. AIR HANDLER POWER ON/OFF MONITORED (CT SWITCH) (CU-4) 12. AIR HANDLER POWER ON/OFF MONITORED (CT SWITCH) (CU-5)	10. EXISTING SYSTEM SHALL BE DISCONNECTED AND INSTALL INSTALL (2) NEW MINI SPLIT SYSTEM IN THE SAME LOCATION. CONDENSING UNIT SHALL BE MOUNTED AT GROUND FLOOR LEVEL USING EXISTING SUPPORTS FROM FLOOR STRUCTURE ABOVE. NEW REFRIGERATION AND CONDENSATE LINES TO FOLLOW THE SAME PATH. VERIFY IN THE FIELD.	
9. SCHEDULING (OCCUPIED/UNOCCUPIED)		11. CONTRACTOR TO PROVIDE DDC CONTROLLER WITH CAPABILITY FOR BACNET INTERFACE CONNECTION. DDC CONTROLLER SHALL ALTERNATE A/C UNITS IN ROOM SUCH THAT ONLY ONE UNIT RUNS AT A TIME. INTERCONNECT WITH NEW ENERGY MANAGEMENT SYSTEM WITH WEB BASED BUI INTERFACE. SEE SEQUENCE OF CONTROLS NOTES FOR MORE DETAILS OF CONSTRUCTION.	
10. SPACE TEMPERATURE		12. PROPOSED LOCATION OF NEW WEB BASED FRONT END ENERGY MANAGEMENT SYSTEM. EXACT LOCATION TO BE ADJUSTED AS REQUIRED IN IT ROOM.	
11. CONDENSER COOLING ON/OFF			
12. CONDENSER HEAT PUMP ON/OFF			



THIS ITEM HAS BEEN DIGITALLY SIGNED AND  
SEALED BY MARK A. BRANT, PE, ON 8/5/2025.  
PRINTED COPIES OF THIS DOCUMENT ARE  
NOT CONSIDERED SIGNED AND SEALED AND  
THE SIGNATURE MUST BE VERIFIED ON ANY  
ELECTRONIC COPIES.

Sheet Number:

M101



Weston & Sampson

Weston & Sampson Engineers, Inc.  
4210 Metro Parkway, Suite 230  
Fort Myers, FL 33919  
239.437.4601 800.SAMPSON  
www.westonandsampson.com

Consultants:

**BURGESS BRANT**  
CONSULTING ENGINEERS  
12955 S. CLEVELAND AVENUE SUITE 229  
FORT MYERS, FL 33912  
(239) 274-0020 (239) 274-0021 (FAX)  
EMAIL: BBCE@BURGESSBRANT.COM  
CERTIFICATE OF AUTHORIZATION #6032  
JOSEPH W. BROUGHTON, PE #63949  
MARK A. BRANT, PE #54692

Revisions:		
No.	Date	Description

COA:

THIS DRAWING  
UTILIZES A DIGITAL  
SIGNATURE LOCATED  
ON G-1

Issued For:

BIDS

Scale:

Date:	8/8/2025
Drawn By:	BBCE STAFF
Reviewed By:	JWBMAB
Approved By:	JWBMAB
W&S Project No.:	ENG25-0284
W&S File No.:	

Drawing Title:

ELECTRICAL  
NOTES &  
SYMBOLS

Sheet Number:

E001

### ELECTRICAL SYMBOL LEGEND

ELECTRICAL DEVICES	
□	GFCI TYPE RECEPTACLE, WALL DUPLEX, 120V, SPECIFICATION GRADE, 20 AMP, INSTALL AT 18" AFF TO C.L. (U.N.O.).
□WP	"WP" SIGNIFIES A WEATHERPROOF WEATHER RESISTANT GFCI RECEPTACLE, WALL DUPLEX, 120 VAC, SPECIFICATION GRADE, 20 AMP. UNO, PROVIDE WITH A METALLIC, "EXTRA DUTY", IN-USE TYPE, WET LOCATION LISTED COVER PLATE.
□	MOTOR DISCONNECT SWITCH, DEAD FRONT MOLDED CASE SWITCH (IF 60 AMPS OR LESS) NON-PROTECTED, NEMA 1 NEMA 3R AS REQUIRED.
□	POWER PANEL (FLUSH/SURFACE) SEE SCHEDULES

### SPECIFIC NOTES

2. VERIFY ROUGH-IN LOCATIONS, TYPE OF CONNECTION, AND AMPACITY REQUIRED FROM APPLICABLE EQUIPMENT DRAWINGS PRIOR TO INSTALLING ANY CONDUIT, CONDUCTORS, OR BOXES. THIS EQUIPMENT IS FURNISHED AND PHYSICALLY INSTALLED BY "OTHERS". ALL ELECTRICAL CONNECTIONS EXTERNAL TO THE EQUIPMENT SHALL BE MADE BY THE ELECTRICAL CONTRACTOR. WIRE, CONDUIT, LUGS, RECEPTACLES, PIG TAILS, DISCONNECTS, AND ETC., AS MAY BE REQUIRED SHALL BE FURNISHED BY THE ELECTRICAL CONTRACTOR. \*\*NOTE: INCLUDE WORSE CONDITION IN PRICING.


### ABBREVIATIONS

A/C	AIR CONDITIONING	KVA	KILOVOLT AMPERE
AC	ALTERNATING CURRENT	KW	KILOWATT
AFF/G	ABOVE FINISH FLOOR/GRADE	N1	NEMA 1 (INDOOR ENCLOSURE)
AHU	AIR HANDLING UNIT	N3R	NEMA 3R (RAIN TIGHT ENCLOSURE)
B	BOND	N/NEUT	NEUTRAL
CB	CIRCUIT BREAKER	NMC	NONMETALLIC CABLE (ROMEX)
Cu	COPPER	NP	NON-PROTECTED
CU	CONDENSER UNIT	P	POWER
DC	DIRECT CURRENT	RS	RIGID STEEL CONDUIT
DISC	DISCONNECT	S/N	SOLID NEUTRAL
EMT	ELECTRICAL METALLIC TUBING (THIN WALL)	SS	STAINLESS STEEL
FC	FAN COIL	UNO	UNLESS NOTED OTHERWISE
G	GROUND	UG	UNDERGROUND
HD	HEAVY DUTY	UL	UNDERWRITERS LABORATORIES
HGT	HEIGHT	WP	WEATHER PROOF
JB	JUNCTION BOX	WR	WEATHER RESISTANT

### GENERAL ELECTRICAL NOTES AND REQUIREMENTS

1. **GENERAL INSTALLATION REQUIREMENTS:**

- THE ELECTRICAL CONTRACTOR SHALL COMPLY WITH THE 2023 FLORIDA BUILDING CODE. THE FLORIDA FIRE PREVENTION CODE (EIGHTH EDITION) WITH CHAPTER 69A-60 APPLICABLE NFPA CODES WHICH INCLUDES THE 2020 NEC (NFPA - 70) AND THE 2021 LIFE SAFETY CODE (NFPA - 101) FLORIDA EDITION.
- THE INSTALLATION OF THE SYSTEMS SHALL BE IN ACCORD WITH THE MATERIALS AND METHODS INDICATED IN THE PLANS AND SPECIFICATIONS. ANY DESIRED DEVIATIONS SHALL BE SUBMITTED (IN WRITING) TO AND APPROVED BY THE ENGINEER. IF NOT INCLUDED IN THE SUBMISSIONS AND NOT SPECIFICALLY REQUESTED, MATERIALS AND METHODS SHALL BE PROVIDED PER PLANS AND SPECIFICATIONS.
- THE CODES REPRESENT THE MINIMUM INSTALLATION CRITERIA FOR THE PROJECT. IT IS THE RESPONSIBILITY OF THE INSTALLING CONTRACTOR TO ADHERE TO THE DESIGN DOCUMENTS SO LONG AS THEY DO NOT INDICATE INSTALLATIONS THAT WILL PRESENT CODE VIOLATIONS. NO ADDITIONAL CHARGES WILL BE APPROVED OR ACCEPTED TO CHANGE THE INSTALLATION IN ORDER TO COMPLY WITH CODE OR TO RETROFIT ANY WORK THAT WAS INSTALLED IN VIOLATION OF A CODE.
- WORK SHALL INCLUDE ALL LABOR, MATERIALS, PERMITS AND COSTS FOR INSTALLATION OF A COMPLETE ELECTRICAL SYSTEM.
- IT IS NOT THE PURPOSE OF THESE PLANS TO SHOW ALL DETAILS OF CONSTRUCTION, ONLY THE INTENT. ELECTRICAL CONTRACTOR IS RESPONSIBLE FOR THE PURCHASE AND INSTALLATION OF ALL ITEMS SUCH AS HARDWARE, J-BOXES, CONDUITS AND FITTINGS, ETC., AS NECESSARY FOR A COMPLETE ELECTRICAL SYSTEM IN WORKING ORDER.
- CONTRACTOR IS RESPONSIBLE FOR PROVIDING COMPLETE BIDS BASED UPON THE ENTIRE SET OF CONSTRUCTION DOCUMENTS. THIS EXTENDS TO ALL DEVICES INDICATED ON PLANS AND ALL EQUIPMENT REQUIRED TO SUPPORT THOSE DEVICES. IF FOR ANY REASON, THE INTENT OF THE ENGINEER, ARCHITECT OR CLIENT IS UNCLEAR THEN THE CONTRACTOR IS TO GET CLARIFICATION PRIOR TO PROVIDING A BID. IF THE CONTRACTOR FAILS TO DO SO, THE CONTRACTOR SHALL BE REQUIRED TO ASSUME ANY ADDITIONAL COSTS INVOLVED IN REALIZING THE INTENT OF THE ENGINEER, ARCHITECT, OR CLIENT.
- ALL EQUIPMENT, FIXTURES, ETC., SHALL BE STARTED, TESTED, ADJUSTED AND PLACED IN SATISFACTORY OPERATING CONDITION BY THIS CONTRACTOR WHO SHALL GUARANTEE ALL WORKMANSHIP, MATERIALS AND EQUIPMENT TO BE FREE OF DEFECTS FOR A PERIOD OF (1) ONE YEAR FROM DATE OF OWNER ACCEPTANCE, AND SHALL REPAIR SUCH DEFECTS WITHOUT COST TO THE OWNER. ALL EQUIPMENT SHALL BE COVERED FOR THE DURATION OF THE MANUFACTURER'S GUARANTEE OR WARRANTY, AND THIS CONTRACTOR SHALL FURNISH THE OWNER WITH ALL MANUFACTURER'S GUARANTEES AND WARRANTIES.
- ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING WITH OTHER PARTIES FOR INSTALLATION OF ALL DEVICES. THIS SHALL INCLUDE (BUT NOT LIMITED TO) THE FOLLOWING:
  - LIGHT FIXTURES AND DEVICES ON INTERIOR AND EXTERIOR OF BUILDING WITH COUNTER TOPS, FURNITURE, WALL FINISHES/CONSTRUCTION, ETC.
  - LIGHT FIXTURES AND DEVICES ON SITE WITH EXISTING/NEW UTILITIES, BUILDINGS/STRUCTURES, PLANTINGS, ETC.
  - ANY INTER-CONNECTIONS BETWEEN ANY OF THE TRADES (HVAC, PLUMBING, FIRE ALARM, FIRE PROTECTION, ARCHITECTURE, ETC.).
- THE ELECTRICAL, HVAC, PLUMBING, FIRE PROTECTION & GENERAL CONTRACTORS SHALL STRICTLY ADHERE TO THE FOLLOWING ITEMS WHEN DEALING WITH ELECTRICAL CLEARANCES:
  - DEDICATED EQUIPMENT SPACE: NO PIPING OF ANY KIND, OR DUCTWORK, SHALL BE INSTALLED ABOVE AN ELECTRICAL SWITCHBOARD OR PANELBOARD. THIS AREA IS TO REMAIN CLEAR FROM THE TOP OF THE EQUIPMENT TO 6' ABOVE THE EQUIPMENT OR TO THE BOTTOM OF THE STRUCTURAL SLAB OR FLOOR, WHICHEVER IS LOWER. ANY PIPING OVER THE EQUIPMENT AND ABOVE THIS HEIGHT SHALL BE FITTED WITH LEAK DEFLECTORS.
  - WORKING SPACE: UNO, A CLEARANCE OF 36" MINIMUM SHALL BE MAINTAINED IN FRONT OF ELECTRICAL EQUIPMENT (OPERATING AT 150 VOLTS OR LESS TO NEUTRAL) FOR A WIDTH OF 30" OR THE ENTIRE WIDTH OF THE EQUIPMENT (WHICHEVER IS LARGER), AND FROM FLOOR TO 6'6" AFF.
  - DO NOT SCALE THE ELECTRICAL DRAWINGS, REFER TO EXISTING CONDITIONS FOR EQUIPMENT LOCATIONS, CABINERY, CEILING, GRID, DOOR SWINGS, ETC.
  - NOTICE TO CONTRACTOR: REVISIONS TO THESE DRAWINGS AND CERTIFICATION THERETO, WHICH MAY BE REQUIRED BY THE APPLICABLE INSPECTION AUTHORITY, BECAUSE OF CONTRACTOR (OR "OTHERS") OPTED REVISIONS SHALL BE COMPENSATED TO THE ENGINEER/S BY THE REQUESTING CONTRACTOR. PAYMENT WILL BE REQUIRED AT TIME OF CERTIFICATION DELIVERY.
  - WITHIN 30 DAYS OF PROJECT COMPLETION, RECORD DRAWINGS (AS BUILT) OF THE PROJECT PROVIDED BY THE CONTRACTOR/S AND SUBMITTED TO THE OWNER. THESE SHALL INCLUDE (MINIMALLY) A SINGLE LINE POWER RISER, PANEL SCHEDULES AND FLOOR PLANS. IN ADDITION OWNER COPIES OF OPERATIONS MANUALS FOR ALL EQUIPMENT REQUIRING SERVICE WITH NAMES AND ADDRESS, AND, CONTACT FOR QUALIFIED SERVICE AGENCY/S.
- IT IS HERE NOTED THAT IF THERE ARE NO CONSTRUCTION OBSERVATION ("CO") TRIPS PERFORMED BY THE ENGINEER/S OF RECORD THERE WILL BE NO CERTIFIED PLANS ("AS BUILT") PROVIDED BY THE ENGINEER/S OF RECORD.
- SUBMITTALS**
- SHOP DRAWINGS SHALL BE PROVIDED FOR ALL ELECTRICAL EQUIPMENT THAT IS TO BE USED ON THIS PROJECT WHETHER OR NOT THE EQUIPMENT IS SPECIFICALLY SPECIFIED IN THESE DOCUMENTS. THIS INCLUDES (BUT IS NOT LIMITED TO) DISTRIBUTION EQUIPMENT, LIGHT FIXTURES, WIRING DEVICES, CERAMIC, CONDUCTORS, CONDUIT, FITTINGS, BOXES, GROUNDING METHODS, ETC.. SHOP DRAWINGS SHALL BE REQUIRED PRIOR TO ORDERING OR ANY INSTALLATION OF EQUIPMENT. ANY EQUIPMENT NOT INCLUDED IN THE SHOP DRAWING SUBMITTALS, SHALL BE PROVIDED PER THE PLANS AND SPECIFICATIONS.
- SUBMITTALS ARE TO BE TOTAL & COMPLETE, INCOMPLETE OR PIECemeAL SHOP DRAWINGS WILL NOT BE REVIEWED UNTIL ALL SUBMITTALS ARE PROVIDED. ALL EQUIPMENT (INCLUDING ANY/ALL OPTIONS) SHALL BE CLEARLY SELECTED/INDICATED ON THE CUTSHEETS INCLUDED IN THE SUBMITTAL.



THIS ITEM HAS BEEN DIGITALLY SIGNED AND  
SEALED BY JOSEPH W. BROUGHTON, PE, ON  
8/5/2025.  
PRINTED COPIES OF THIS DOCUMENT ARE  
NOT CONSIDERED SIGNED AND SEALED AND  
THE SIGNATURE MUST BE VERIFIED ON ANY  
ELECTRONIC COPIES.

Sheet Number:

E001






Weston &amp; Sampson


Weston & Sampson Engineers, Inc.  
4210 Metro Parkway, Suite 230  
Fort Myers, FL 33919  
239.437.4601 800.SAMPSON  
www.westonandsampson.com

Consultants:


**BURGESS BRANT**  
CONSULTING ENGINEERS  
12955 S. CLEVELAND AVENUE SUITE 229  
FORT MYERS, FL 33912  
(239) 274-0021 (FAX)  
EMAIL: BBC@BURGESSBRANT.COM  
CERTIFICATE OF AUTHORIZATION #6032  
JOSEPH W. BROUGHTON, PE #63949  
MARK A. BRANT, PE #54692




**EXISTING PANEL "CCU" SCHEDULE**  
225 AMP BUS - MLO - 120/208V - 3 PHASE - S/N  
44 CIRCUIT - SURFACE MOUNTED - NEMA 3R  
PANEL BOARD (SQ-D NOOB) WITH COPPER BUS




**EXISTING PANEL "CCU" SCHEDULE**  
100 AMP BUS - MLO - 120/208V - 3 PHASE - S/N  
24 CIRCUIT - SURFACE MOUNTED - NEMA 3R  
PANEL BOARD (SQ-D NOOB) WITH COPPER BUS




**EXISTING PANEL "EM" SCHEDULE**  
225 AMP BUS - MLO - 120/208V - 3 PHASE - S/N  
44 CIRCUIT - SURFACE MOUNTED - NEMA 1  
PANEL BOARD (SQ-D NOOB) WITH COPPER BUS




**EXISTING PANEL "EM" SCHEDULE**  
600 AMP BUS - MLO - 120/208V - 3 PHASE - S/N  
SURFACE MOUNTED - NEMA 1  
PANEL BOARD (---) WITH COPPER BUS




**REWORKED PANEL "CCU" SCHEDULE**  
225 AMP BUS - MLO - 120/208V - 3 PHASE - S/N  
44 CIRCUIT - SURFACE MOUNTED - NEMA 1  
PANEL BOARD (---) WITH COPPER BUS




**REWORKED PANEL "CCU" SCHEDULE**  
100 AMP BUS - MLO - 120/208V - 3 PHASE - S/N  
20 CIRCUIT - SURFACE MOUNTED - NEMA 1  
PANEL BOARD (---) WITH COPPER BUS




**POWER RISER DIAGRAM**  
NOT TO SCALE




**EXISTING PANEL "EM2" SCHEDULE**  
1,200 AMP BUS - MLO - 120/208V - 3 PHASE - S/N  
SURFACE MOUNTED - NEMA 1  
PANEL BOARD (---) WITH COPPER BUS



**REWORKED PANEL "EM2" SCHEDULE**  
100,000 AIC RATED  
1,200 AMP



**EXISTING PANEL "M" SCHEDULE**  
1,200 AMP EXISTING




**EXISTING PANEL "M" SCHEDULE**  
1,200 AMPS EXISTING

**EXISTING PANEL "M" SCHEDULE**  
HIGHEST RECORDED DEMAND @ 125% = 106.0 KVA

**NEW PANEL "C" LOADS**  
= 31.6 KVA

**1,200 AMPS EXISTING**  
( $\sqrt{3} \times 208$ )  $\div$  360 V = 382.0 AMPS

<b>POWER RISER DIAGRAM KEYNOTES</b>	
1.	EXISTING LEOG TRANSFORMER, 120/208 VOLT, 3-PHASE. NO CHANGES.
2.	(3) EXISTING SETS OF (3) #500, (1) #350 MCM-N, NO CHANGES.
3.	EXISTING GROUNDING SYSTEM, NO CHANGES.
4.	EXISTING C/T METER, NO CHANGES.
5.	EXISTING C/T CABINET, NO CHANGES.
6.	EXISTING 600 AMP, 120/208 VOLT ATS, NO CHANGES.
7.	EXISTING 125KVA EMERGENCY GENERATOR, NO CHANGES.
8.	(2) EXISTING SETS OF (4) #350 kcmil Cu, (1) #1 Cu-G, NO CHANGES.
9.	EXISTING (4) #250 MCM, NO CHANGES.
10.	EXISTING (4) #1 Cu, (1) #6 Cu-G, NO CHANGES.



THIS ITEM HAS BEEN DIGITALLY SIGNED AND  
SEALED BY JOSEPH W. BROUGHTON, PE, ON  
8/5/2025.  
PRINTED COPIES OF THIS DOCUMENT ARE  
NOT CONSIDERED SIGNED AND SEALED AND  
THE SIGNATURE MUST BE VERIFIED ON ANY  
ELECTRONIC COPIES.