

```
LEE COUNTY, FLORIDA
```

634 N YACHTSMAN DR

DREDGE PERMIT PLANS

SANIBEL, LEE COUNTY, FLORIDA TOWNSHIP: 46S, RANGE: 21E, SECTION 02



PROJECT LOCATION 634 N YACHTSMAN DR, SANIBEL, FLORIDA 33957

NOTES:


- 1. COORDINATES SHOWN ARE IN FEET BASED ON THE NORTH AMERICAN DATUM OF 1983, WEST ZONE (NAD83)
- 2. ELEVATIONS SHOWN ARE IN FEET BASED ON THE NORTH AMERICAN VERTICAL DATUM OF 1988 (NAVD88)
- THE VERTICAL DATUMS ESTABLISHED BY DEP FOR THIS AREA ARE: MEAN HIGH WATER 3.
- ELEVATION & MEAN LOW WATER ELEVATION AS DETAILED IN THE TIDE INFORMATION CHART. NOTE: THESE PERMIT DRAWINGS SHALL NOT BE CONSIDERED VALID FOR CONSTRUCTION 4. PURPOSES UNLESS SIGNED AND SEALED BY:

JOSEPH T. FOSTER. P.E. FL LIC# 79708

NOT VALID UNLESS SIGNED & SEALED

					FRC	FROM TIDE STATION OB LAINED FROM TIDE STATION I.D. 8725393, ST. JAMES CITY,PINE ISLAND FL			
	FOSTER CONSULTING	REVISION	DESCRIPTION	REVISION DATE		DATE:		REV:	
	FL PROFESSIONAL ENGINEER NO. 79708	Λ	ADDED MANGROVES, DOCK / WALL CALCULATIONS	06/20/24	634 N YACHTSMAN DR	04/12/24 DRAWN BY:	SHEET:		
FOSTER	DE LIC. # 18618 · NJ LIC. # 24GE05181200 · TX LIC. # 133648	\triangle			SANIBEL, FLORIDA	BRT	-	DF 11	
CONSULTING	FL CERTIFICATE OF AUTHORIZATION NO. 32050	\triangle				CHECKED BY:			
CONSOLITING	WWW.JFOSTERCONSULTING.COM	\land			COVER SHEET	JTF SCALE:		1	
	P: (727) 821-1949 2963 1ST AVE. S., ST. PETERSBURG, FL 33712	$\overline{\Delta}$				AS NOTED	_	′■	

	SHEET INDEX			
	GENERAL INFORMATION			
01	COVER SHEET			
02	GENERAL NOTES			
	PLANS & DETAILS			
03	AERIAL SITE PLAN			
04	DREDGE PLAN			
05	DREDGE PLAN			
06	DREDGE PLAN			
07	DREDGE SECTIONS			
08	DREDGE SECTIONS			
09	DREDGE SECTIONS			
10	DREDGE SECTIONS			
11	DREDGE SECTIONS			



SPECIFICATIONS

1.TURBIDITY

1a. Turbidity will be minimized for both magnitude and duration to the maximum extent practicable. 1b. Turbidity at the outside edge of the project area shall not exceed federal and state water standards. 1c. Management practices and suitable technology are implemented for all stationary installations including those created for drainage, flood control, or by dredging or filling; and there is no alternative to the proposed activity, including the alternative of not undertaking any change, except at an unreasonably higher cost. 1d. A turbidity curtain shall be used only during in-water work to minimize any potential impacts on natural resources.

2. DE-WATERING

2a. De-watering of dredged materials will take place on the construction barge.

3. OFFLOAD SITE

3a. Once materials are de-watered they will be hauled to a spoil site determined by the contractor in sealed trucks.

4. LOADING/UNLOADING


4a. Loading and unloading of equipment will take place on land at the western end of the project area.

5. The contractor shall provide access to the canal as requested and only at times when the water quality within the project area does not exceed water quality standards.

6. DREDGING METHODOLOGY

6b. Mechanical Dredging Methodology: Prior to dredging, a floating turbidity boom will be installed around the proposed dredge area. The boom will be secured to the shoreline on each side of the project and will maintain contact to the bottom at all times. The boom will be secured to the shoreline on each side of the project and will maintain contact to the bottom at all times. The boom shall be maintained throughout dredging activities. Two monitoring stations will be established to monitor turbidity containment. Water testing and reporting will be conducted as required per permit stipulations throughout the dredging activities. The turbidity boom shall be left in place until all suspended sediments have fallen out of the water column and the water within the area meets state water quality standards, at which point it will be removed. The dredge material will be loaded into a container on a barge using barge based excavator, and will be transported to the offloading site along the shoreline/parking lot for unloading. The offloading site will have staked silt fences and hay bales to prevent any sediment runoff during the offloading activities. The dredge material will be placed into sealed trucks using a land based excavator and will be transported to an off-site spoil site. The spoil disposal site will have staked silt fences and hay bales to prevent any sediment runoff. No discharge or return water will be allowed to reach wetlands or nearby water bodies. OR 6c. Hydaulic Dredging Methodology: Dredging may be performed using a hydraulic dredge pump. This hydraulic pump will then pump the slurry to sealed (watertight) containers that will be staged near the terminal end of the canal. The settling containers will be monitored continuously to ensure the capacity of the containers are not exceeded. The dredged sediments will be dewatered within the settling containers through gravity settling. A baffle system will be used to allow the water to spill over and then be piped back to the original dredge area. This process will be monitored to ensure dredged material and/or return water will not spill and enter stormwater drains. An alternative approach will be using a geotube within the container, the sediments will be filtered through the tube. The return water from the geotube would be piped back into the original dredge area. Hay bales are proposed at either end of the containers in series and surrounding any stormwater catch basin. The project areas will be left clean and returned to previous conditions.

NOT VALID UNLESS SIGNED & SEALED









FOSTER CONSULTING FL PROFESSIONAL ENGINEER NO. 79708 DE LIC. # 18618 · NJ LIC. # 24GE05181200 · TX LIC. # 133648 FL CERTIFICATE OF AUTHORIZATION NO. 32050 WWW.JFOSTERCONSULTING.COM


P: (727) 821-1949 2963 1ST AVE. S., ST. PETERSBURG, FL 33712


	REVISION DATE	DESCRIPTION	REVISION
634 N YAC	06/20/24	ADDED MANGROVES, DOCK / WALL CALCULATIONS	\mathbb{A}
SANIBEI			\triangle
			\triangle
GENER			\triangle
			\triangle

TYP. TURBIDITY CURTAIN DETAIL

LOADING/UNLOADING AREA

REV:
F 11
2







 Δ


DREDG

	DATE:	FILE:	REV:
CHTSMAN DR	04/12/24	240XXX	
EL. FLORIDA	DRAWN BY:	SHEET:	
	BRT	04 0	F 11
	CHECKED BY:		
	JTF	Δ	4
GE PLAN 01	SCALE:	U	4
	AS NOTED		





CHTSMAN DR	DATE:	FILE: REV: 240XXX
	DRAWN BY:	SHEET:
	BRT	05 OF 11
	CHECKED BY:	
	JTF	ΛE
GE PLAN 02	SCALE:	05
	AS NOTED	







	DATE:	FILE:	REV:
CHTSMAN DR	04/12/24	240XXX	
EL. FLORIDA	DRAWN BY:	SHEET:	
	BRT	06 O	F 11
	CHECKED BY:		
	JTF	0	6
GE PLAN 03	SCALE:	U	D
	AS NOTED		










	DATE:	FILE:	REV:
ACHTSMAN DR	04/12/24	240XXX	
EL. FLORIDA	DRAWN BY:	SHEET:	
	BRT	07 0	F 11
	CHECKED BY:		
	JTF	Δ	7
E SECTIONS	SCALE:	U	
	AS NOTED		










SCALE:		
JTF	Δ	Ω
CHECKED BY:		
BRT	08 O	F 11
DRAWN BY:	SHEET:	
04/12/24	240XXX	
DATE:	FILE:	REV:
	04/12/24 DRAWN BY: BRT CHECKED BY: JTF	04/12/24 240XXX DRAWN BY: SHEET: BRT 08 0 CHECKED BY: JTF









	DATE:	FILE:	REV:
ACHTSMAN DR	04/12/24	240XXX	
BEL, FLORIDA	DRAWN BY:	SHEET:	
	BRT	09 0	F 11
	CHECKED BY:		
	JTF	Δ	0
E SECTIONS	SCALE:	0	J
	AS NOTED		



SECTION 01
647± SF
41' LF (A.O.I.)
±982.5 CUBIC YARDS



	AS NOTED		
E SECTIONS	SCALE:		V
	JTF	1	
BEL, FLORIDA	CHECKED BY:		
	BRT 10 OF 1		
	DRAWN BY:	SHEET:	
ACHTSMAN DR	04/12/24	240XXX	
	DATE:	FILE:	REV:





	FOSTER CONSULTING	REVISION	DESCRIPTION	REVISION DATE	
			ADDED MANGROVES, DOCK / WALL CALCULATIONS	06/20/24	634 N YA
	FL PROFESSIONAL ENGINEER NO. 79708	$\underline{\Lambda}$	ADDED MANGHOVES, DOCK / WALL CALCOLATIONS	00/20/24	SANIBE
FOSTER	DE LIC. # 18618 · NJ LIC. # 24GE05181200 · TX LIC. # 133648	Δ			
CONSULTING	FL CERTIFICATE OF AUTHORIZATION NO. 32050 WWW.JFOSTERCONSULTING.COM				
	P: (727) 821-1949	Δ			DREDGE
	2963 1ST AVE. S., ST. PETERSBURG, FL 33712	Δ			

NOT VALID UNLESS SIGNED & SEALED

-

	DATE:	FILE:	REV:
CHTSMAN DR	04/12/24	240XXX	
EL, FLORIDA	DRAWN BY:	SHEET:	
	BRT	11 OF 11	
E SECTIONS	CHECKED BY:		
	JTF	4	4
	SCALE:		
	AS NOTED		

